



HFMED®

HF-L25

Shadowless Operating lamp

Uniform, homogeneous lighting in surface and deep cavity procedures thanks to HF-L125's innovative shadow control.

Our ergonomic, sterile operating concept allows for the simple and flexible control of all functions by the surgical team.

Almost unlimited LED life expectancy delivers tremendous product reliability and investment protection.

Environmentally proactive: low power consumption and durable LEDs minimize the impact on our precious resources.



WHY CHOOSE US



OUR ADVANTAGE

The company keeps to the concept of being oriented by science and technology and taking quality as life. Now the company has passed the certification of ISO9001:2008, ISO13485:2003, CE and SGS.



MANAGEMENT

"Quality first, Credit first, Service first" is our tent. Huifeng are looking forward to sincere cooperation with you. Let's advance and pursue a wonderful future by mutual efforts.



SALES MARKET

all has its domestic sales amount coming out at the top and some products have ready sale in Southeast Asia. Its products can be found in all the domestic markets in China and also are sold abroad.



Official QR code



HFMED®


YOUR IDEAL OPERATING LIGHT SUPPLIER
SHANGHAI HUIFENG MEDICAL INSTRUMENT CO., LTD.
 Address: NO 885, QiuXing Road, Nicheng Town, Pudong New Area, Shanghai, China.
 Tel: +86-021-58084992
 Mob: +86-17717536508
 Email: huifeng6@huifeng-co.com
 web: http://en.huifeng-co.com



HF-L25
Shadowless Operating lamp

HFMED


SHANGHAI HUIFENG MEDICAL INSTRUMENT CO., LTD



HF-L25

SHADOW LESS OPERATING LAMP


- Precise
Uniform, homogeneous lighting in surface and deep cavity procedures thanks to HF-L25's innovative shadow control
- Simple
Our ergonomic, sterile operating concept allows for the simple and flexible control of all functions by the surgical team.
- Durable
Almost unlimited LED life expectancy delivers tremendous product reliability and investment protection.
- Efficient
Environmentally proactive: low power consumption and durable LEDs minimize the impact on our precious resources.



LED light source does not produce infrared, the temperature rise above surgeon's head is less than 2°C.

Main Technical Data

HF-L25	Shadowless Operating lamp
Illuminance	≥70,000Lux
Colour temperature	3800±200K, 4800±200K
Colour reduction index(Ra)	92
Illuminance depth	700mm
Total irradiance	380W/ m ²
Size of light field	150mm
Lamp head diameter	300mm
Rated power of bulb	3.2V/1W
Service life of illuminance	≥50,000h
Power supply voltage	AC110-240V,50/60Hz
Total power consumption	30W
Total LED bulb quantity	25 pcs



LED light source life of up to 50,000 hours or more, with an average life of an ordinary light shadowless lamp halogen 30 times, and each LED can be individually replaced, to ensure maximum use of economy.